

## Declaration of performance

No. 4 - 220/105/65 (Valid from 01.05.2020)

E: INFO@PETERSEN-TEGL.DK  
 P: +45 7444 1236  
 W: PETERSEN-TEGL.DK

1. **Unique identification code of the product type:** D43-D46-D47-D48-D49-D55-D58-D96-D97-D99-D199
2. **Intended use/es:** U unit for use in unprotected masonry
3. **Manufacturer:** Petersen Tegl A/S, Nybølnorvej 14, DK-6310 Broager
4. **Authorized representative:** Not applicable
5. **System/s of AVPC:** System 2+
6. **Harmonized standard:** EN 771-1:2011+A1:2015
- Notified body/ies:** NB 1073
7. **Declared performance/s:**

Essential Characteristics		Performance	
Dimensions	Length/width/height (mm)	220/105/65	
Dimensional tolerances	Mean value	T1	
	Range	NPD*	
Configuration	Group according to EN 1996-1-1, table 3.1	G1	
Compressive strength	Category	1	
	Mean value	≥15 N/mm <sup>2</sup>	
	Normalised	≥12 N/mm <sup>2</sup>	
	Direction of load	Parallel to the bed surface	
Dimensional stability	Moisture movement	NPD*	
Bond strength (according to EN 998-2, Appendix C)		NPD*	
Active soluble salts content		S2	
Reaction to fire		A1	
Water absorption		NPD*	
Water vapour permeability		NPD*	
Direct airborne sound insulation	Gross dry density	Mean value	NPD*
		Tolerance	NPD*
Thermal resistance		NPD*	
Durability against freeze/thaw		F2	
Dangerous substances		NPD*	

\* No performance determined

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Broager, 01.05.2020

  
 CFO Poul M. Kjeldsen



NB 1073

Petersen Tegl A/S, Nybølnorvej 14, DK-6310 Broager

17

Declaration of performance No. 4 - 220/105/65 (Valid from 01.05.2020)

EN 771-1:2011+A1:2015

D43-D46-D47-D48-D49-D55-D58-D96-D97-D99-D199

U unit for use in unprotected masonry

Category 1

Dimensions	Length/width/height (mm)	220/105/65	
Dimensional tolerances	Mean value	T1	
	Range	NPD*	
Configuration	Group according to EN 1996-1-1, table 3.1	G1	
Compressive strength	Category	1	
	Mean value	≥15 N/mm <sup>2</sup>	
	Normalised	≥12 N/mm <sup>2</sup>	
	Direction of load	Parallel to the bed surface	
Dimensional stability		NPD*	
Bond strength (according to EN 998-2, Appendix C)		NPD*	
Active soluble salts content		S2	
Reaction to fire		A1	
Water absorption		NPD*	
Water vapour permeability		NPD*	
Direct airborne sound insulation	Gross dry density	Mean value	NPD*
		Tolerance	NPD*
Thermal resistance		NPD*	
Durability against freeze/thaw		F2	
Dangerous substances		NPD*	

\* No performance determined

## UK Declaration of performance

No. UK4 - 220/105/65 (Valid from 22.08.2022)

Certificate Number: 0086-CPR-766512

1. **Unique identification code of the product type:** D43-D46-D47-D48-D49-D55-D58-D96-D97-D99-D199
2. **Intended use/es:** U unit for use in unprotected masonry
3. **Manufacturer:** Petersen Tegl A/S, NybølNorvej 14, DK-6310 Broager
4. **Authorized representative:** Not applicable
5. **System of assessment and verification of constancy of performance of the construction product:** System 2+
6. **UK designated standard:** BS EN 771-1:2011+A1:2015  
**UK approved body:** 0086 (BSI Assurance UK Ltd)

7. **Declared performance:**

Essential Characteristics		Performance	
Dimensions	Length/width/height (mm)	220/105/65	
Dimensional tolerances	Mean value	T1	
	Range	NPD*	
Configuration	Group according to EN 1996-1-1, table 3.1	G1	
Compressive strength	Category	1	
	Mean value	≥15 N/mm <sup>2</sup>	
	Normalised	≥12 N/mm <sup>2</sup>	
	Direction of load	Parallel to the bed surface	
Dimensional stability	Moisture movement	NPD*	
Bond strength (according to EN 998-2, Appendix C)		NPD*	
Active soluble salts content		S2	
Reaction to fire		A1	
Water absorption		NPD*	
Water vapour permeability		NPD*	
Direct airborne sound insulation	Gross dry density	Mean value	NPD*
		Tolerance	NPD*
Thermal resistance		NPD*	
Durability against freeze/thaw		F2	
Dangerous substances		NPD*	


\* No performance determined

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with UK legislation Construction Products Regulations 2019 No. 465, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Broager, 22.08.2022

  
 CFO Poul M. Kjeldsen

 0086 (BSI Assurance UK Ltd) Petersen Tegl A/S, NybølNorvej 14, DK-6310 Broager 22			
BS EN 771-1:2011+A1:2015			
D43-D46-D47-D48-D49-D55-D58-D96-D97-D99-D199 U unit for use in unprotected masonry Category 1			
Dimensions	Length/width/height (mm)	220/105/65	
Dimensional tolerances	Mean value	T1	
	Range	NPD*	
Configuration	Group according to EN 1996-1-1, table 3.1	G1	
Compressive strength	Category	1	
	Mean value	≥15 N/mm <sup>2</sup>	
	Normalised	≥12 N/mm <sup>2</sup>	
	Direction of load	Parallel to the bed surface	
Dimensional stability		NPD*	
Bond strength (according to EN 998-2, Appendix C)		NPD*	
Active soluble salts content		S2	
Reaction to fire		A1	
Water absorption		NPD*	
Water vapour permeability		NPD*	
Direct airborne sound insulation	Gross dry density	Mean value	NPD*
		Tolerance	NPD*
Thermal resistance		NPD*	
Durability against freeze/thaw		F2	
Dangerous substances		NPD*	

\* No performance determined